

# Chest freezer XLT C150



- Low cost of ownership
- Limited maintenance and on-site service
- Easily installable & movable

- Efficient cyclopentane insulation
- Eco-friendly, HCFC-free Nature R refrigerant
- ISO 9001, 14001 & 18001 OHSAS Certified

Specifications	
<b>Technical</b>	
Gross volume	140 litres
Net Volume	133 litres
Temp. range	-30°C to -65°C
Temp. probes	1/PT 1000
Compressor	Embraco
Baskets (incl./optional)	1/2
Refrigerant	Nature R
Noise level	55 dB
Power consumption 24/h	3,7 kWh
Power consumption	1.350 kWh / year
Voltage	230V
Frequency	50 Hz
<b>Features</b>	
Audible and visual alarm	YES
Castors	4
Integrated lock	YES
Inner lids	NO
Defrost	Manual
Battery Backup	NO
USB	NO
Data connection	NO
Digital controller with display	XR30CX
Data logging	NO
High/Low temperature alarm	YES
Porthole for external probe & CO2 backup	Ø12 mm
Prepared for external logging equipment	YES
<b>Material</b>	
Inner	Precoated white steel
Outer	Galvanized pre-coated steel
<b>Outer dimensions</b>	
Height (with castors)	890 mm
Width	720 mm
Depth (incl. condenser)	630 mm
Depth (incl. condenser & handle)	680 mm
Net weight	56 kg
<b>Inner dimensions</b>	
Height	635/385 mm
Width	350/210 mm
Depth	440 mm
Insulation	80 mm
Insulation type	PUR
Internal humidity	<5 %

**XLT C150**



**Product no.** N112002

Storage capacity				
Box height	No. of boxes	No. of racks	Total no. of boxes	Product no.
50 mm	6	3	18	N311200
	11	6	66	N311220
			<b>= 84</b>	
75 mm	4	3	12	N311300
	8	6	48	N311320
			<b>= 60</b>	
100 mm	3	3	9	N311400
	5	6	30	N311420
			<b>= 39</b>	

Akralab SL  
 Polígono Industrial Las Atalayas  
 Avda. de la Antigua Peseta 77  
 03114 Alicante

Tel: 965 116 521  
 E-mail: [atencion.clientes@akralab.es](mailto:atencion.clientes@akralab.es)  
 Web: [www.akralab.es](http://www.akralab.es)

